

TECHNICAL DATA SHEET

Date of issue: 2020

SONETTO

DESCRIPTION

Decorative paint of distinct style that transforms the room, giving a special color harmony.



TECHNICAL CHARACTERISTICS	
Density	: 1,00 - 1,02 (ЕЛОТ EN ISO 2811 20°C)
Viscosity	: 15.500 – 17.500 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 7 - 9 m ² /lt per layer
	With substrate LEGGENDA $3 - 5m^2/lt$
Drying time	: Touch dry after 1 hour
Colors	: Many shades through color card of MONDOBELLO
Packaging	: 750ml, 3lt
VOC (Volatile Organic	: EU limit value for this product Category A: "l", Type:WB, Decorative
Compounds)	effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Brush, special glove, plastic spatula
	Remove as much paint as possible from the equipment in the container
	and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every
	use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

It is applied with a brush or a special glove by making circular or irregular movements. Before drying, we create the final effect by gently moving with the special spatula or glove all over the surface.

For a richer effect before applying SONETTO we apply a layer of decorative paint LEGGENDA diluted up to 20%.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.